

Creating Multi-associative Memory in Cell Assemblies

Kailash Nadh

Supervisors: Supervisors

November 2009



School of Engineering and Information Sciences
Middlesex University

Abstract

 Lorem ipsum dolor sit amet, consectetur adipiscing elit. Nullam placerat ullamcorper augue, eget auctor velit ornare vitae. Fusce id elit ac lorem posuere tincidunt et sit amet felis. Quisque varius metus tellus. Proin volutpat laoreet nunc, in hendrerit metus ornare vel. Phasellus eleifend enim quis leo pretium vehicula laoreet dolor pulvinar. In ante mi, imperdiet gravida euismod feugiat, scelerisque quis eros. In molestie, leo et vulputate dignissim, tellus est laoreet risus, at semper est mi ac sem. Mauris ut velit ipsum, nec gravida dui. Aliquam mi metus, fringilla non condimentum sed, venenatis nec massa. Suspendisse semper luctus turpis, vitae venenatis lorem convallis quis. Vestibulum ante ipsum primis in faucibus orci luctus et ultrices posuere cubilia Curae; Suspendisse eget convallis eros. Pellentesque vitae nisl ac arcu sollicitudin rhoncus eget at arcu. Fusce nulla odio, scelerisque quis pretium in, venenatis sit amet augue. Mauris id elit mauris. Aenean egestas faucibus turpis, a mollis enim gravida vel. In ullamcorper rutrum feugiat.

Contents

Abstract	ii
List of Tables	iii
List of Figures	iv
1 Introduction	1
2 Background	2
2.1 Cell Assemblies	2
2.2 Associative memory	2
2.3 Multi-associative memory	3
2.4 CAs and auto-associative memory	3
2.5 Related work	3
2.5.1 Nullam facilisis	3
2.5.2 In consequat	3
3 Work so far	4
3.0.3 Section 1	4
3.0.4 Section 2	4
4 Conclusion	5
4.1 Future work	5
4.2 Timeline	5
References	5

List of Tables

List of Figures

Chapter 1

Introduction

Vivamus non nunc nibh, id malesuada ante. Donec commodo nisi a nulla cursus varius at ac sem. Etiam rutrum, mi ut fermentum accumsan, eros dui gravida arcu, quis dignissim neque magna sed eros. Ut nec lectus a nisi viverra auctor non a arcu. Sed ante ante, sagittis varius tincidunt eu, blandit a risus. In justo tellus, molestie nec tristique vitae, tempor ac dolor. Quisque est felis, imperdiet vel convallis ut, dapibus nec quam. Nulla pharetra faucibus ullamcorper. Nulla facilisi. Morbi et nulla a lectus fringilla suscipit in non neque. Integer placerat bibendum odio et varius. Sed et ipsum nulla, vel pellentesque odio. Vivamus id neque lectus, tincidunt condimentum velit. Etiam nec magna quis libero blandit aliquet. Curabitur erat odio, tempor ut cursus eget, elementum non ante. Mauris quis suscipit odio. Maecenas id risus egestas ante dictum ultricies vitae turpis.

Phasellus scelerisque, risus eget consequat dapibus, urna mauris pulvinar erat, a suscipit nulla tortor at risus. Vivamus euismod urna laoreet magna hendrerit in consectetur sem hendrerit. In convallis dolor ac neque consequat a aliquam arcu hendrerit. Integer vitae faucibus neque. Mauris ac velit leo, id scelerisque massa. Duis sed odio in erat tempus volutpat. Praesent in dignissim dui. Curabitur ac malesuada orci. Maecenas at tellus eu massa aliquam tempor. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Duis vitae quam felis. Mauris non tortor non lectus ullamcorper aliquet sed ac sem. Duis nec tortor dui, nec mattis metus. Vivamus sapien elit, mollis at fringilla nec, vehicula sed diam. Vivamus egestas euismod magna eu rutrum.

Chapter 2

Background

Nullam facilisis arcu eget metus fringilla vitae lacinia diam fermentum. Fusce ligula nisi, euismod ut pulvinar non, blandit a leo. Fusce purus sem, vulputate et aliquet et, aliquam eu tortor. Morbi eget tortor nulla, quis tincidunt erat. Etiam ut enim ut velit luctus dignissim ut a lectus. Vivamus at vestibulum est. Morbi pulvinar nunc in ipsum placerat auctor. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut ante purus, congue in suscipit vitae, feugiat at augue. Donec lectus magna, imperdiet at iaculis vitae, tincidunt non sapien. Nullam eget nibh elit, ac euismod orci. Vestibulum ante ipsum primis in faucibus orci luctus et ultrices posuere cubilia Curae; Sed gravida lacinia libero ac accumsan. Class aptent taciti sociosqu ad litora torquent per conubia nostra, per inceptos himenaeos. Ut ut leo urna. Sed sit amet erat augue. Fusce rhoncus pulvinar leo, a tempus odio blandit eu. Lorem ipsum dolor sit amet, consectetur adipiscing elit.

2.1 Cell Assemblies

(Hebb, 1949) hypothesised that the CA is the neural basis of concepts, and the CA is central to most neural models of memory. The theory proposes that objects, ideas, stimuli and even abstract concepts are represented in the brain by simultaneous activation of large groups of neurons with high mutual synaptic strengths (Wennekers and Palm, 2000). If an external stimulus excites a sufficient number of neurons of an existing CA, it can result in the spreading of activation within the CA, in turn igniting it due to recurrent activity and high mutual synaptic strength. The CA can remain active even after the stimulus is removed. This reverberating behaviour accounts for short term memory.

CAs are learned using the Hebbian learning rule, whereby modifications in the synaptic transmission efficacy are driven by the correlations in the firing activity of pre-synaptic and post-synaptic neurons (Gerstner and Kistler, 2002). When external stimuli are presented to a network, synaptic strength between neurons are adjusted so as to gain more strength if they undergo repeated and persistent activation or firing, gradually assembling them into a group, a CA. This formation of CAs accounts for long term memory. Thus, the CA hypothesis provides a structural and functional account for such cortical processes. A significant amount of evidence exists supporting the fact that CAs are the neural basis of concepts (Huyck and Nadh, 2009).

2.2 Associative memory

Even though CAs account for memory formation, their precise neural dynamics are far from perfectly understood. As explained in the Section ??, neurons in a network may belong to different CAs, and if they are repeatedly co-activated by different versions of the same stimulus, they tend to become associated Hebb (1949). This is based

on the notion that events that occur together repeatedly should somehow belong together. (Wennekers and Palm, 2000) explained that every time these events occur in conjunction, they drive certain subgroups of neurons, their correlated firing should be learned, and, by that, respective groups should become associatively connected.

Repeated co-activation of neurons can lead to the formation of CAs. Similarly, repeated co-activation of multiple CAs result in the formation of multiple and sequential associations, and sometimes new CAs. When an external stimulus activates a CA, it might lead to the activation of neurons that ignites a different CA that is not directly stimulated. This forms the rudimentary, neural level explanation of associative memory. Humans constantly retrieve and form associations with whatever sensory input they receive for the purpose of perception, understanding and reasoning.

2.3 Multi-associative memory

Auto-associative memory is not typically what is meant by associative memory. Instead, associative memory is generally a shortened form (usually implicitly) of multi-associative memory; this has also been called hetero-associative memory. Psychologically, memories are not stored as individual concepts, but large collections of associated concepts that have many to many connections Anderson and Bower (1980). Each memory (CA) is associated with many other memories (CAs) (Huyck and Nadh, 2009).

2.4 CAs and auto-associative memory

The CA is a form of auto-associative memory. In auto-associative memories, an initial state is allowed to settle into a stored memory, allowing subsequent noisy input to retrieve a stored pattern. The Hopfield Model illustrates this property (Hopfield, 1984). A network of units that are well connected with bidirectional weighted connections is used to store a set of binary patterns (typically using a Hebbian calculation). When an initial set of neurons is switched on, in the discrete version of the system, activation spreads through the system based on the weighted connections. In most cases the system will settle into a stable state with no neurons switching between on and off. If the input pattern is close to a stored pattern, it will settle into that pattern's state, thus functioning as a content-addressable memory. Neurons may also belong to multiple CAs. Hopfield patterns that share on-bits are models of CAs that share neurons.

While CAs are critical for the model of multi-associative memory described in this paper, they are not the solution. The question is how different CAs are associated with each other.

2.5 Related work

2.5.1 Nullam facilisis

2.5.2 In consequat

Models are described in detail in Chapter 3

Chapter 3

Work so far

3.0.3 Section 1

3.0.4 Section 2

Chapter 4

Conclusion

4.1 Future work

4.2 Timeline

Bibliography

- John Robert Anderson and Gordon H. Bower. *Human Associative Memory: A Brief Edition*. Lawrence Erlbaum Associates, USA, 1980.
- W. Gerstner and W. K. Kistler. Mathematical formulations of hebbian learning. *Biological Cybernetics*, 87(5-6): 404–415, 2002.
- Donald O. Hebb. *The organization of behavior*. Wiley, New York, 1949.
- J. J. Hopfield. Neurons with graded response have collective computation properties like those of two-state neurons. In *Proceedings of the National Academy of Sciences*, volume 81, pages 3088–3092, 1984.
- C. Huyck and K. Nadh. Multi-associative memory in flif cell assemblies. In R. Cooper (Eds.) A. Howes, D. Peebles, editor, *9th International Conference on Cognitive Modeling ICCM2009*, Manchester, UK, 2009.
- T. Wennekers and G. Palm. Cell assemblies, associative memory and temporal structure in brain signals. In *R.Miller, editor, Time and the Brain. Conceptual advances in Brain Research, Vol. 2*. Harwood Academic Publishers, 2000.